

Ashok Alco - chem Limited (AACL)

MSDS

	Ethyl Acetate	Glacial Acetic Acid	Acetaldehyde
Hazards identification	 Flammable Liquid and Vapor Harmful in contact with skin and also by inhalation. Irritation to skin, eye, respiratory tract. 	 Flammable corrosive liquid and vapor. Liquid and mist causes severe burns to all body tissues. Inhalation may cause lung and tooth damage. Irritation to skin, eye, respiratory tract. 	 Extremely flammable Harmful if swallowed Inhalation of vapors may cause asphyxiation, nausea, vomiting. Irritation to skin, eye, respiratory tract.
Materials for packaging	Stainless Steel / Mild Steel Tanks and Tankers	 Stainless steel, aluminum, polyethylene, polypropylene containers. Avoid: steel, iron, zinc, lead, copper, bronze 	Mild Steel Pressure Tank or Cylinder with Pressure Valve and Nitrogen Blanket
Suitable fire extinguishing media	 Alcohol foam / Water spray Polyvalent foam / BC powder Carbon dioxide 		
Special protective equipment for fire fighters	 Compressed air / oxygen apparatus Gas tight suits Protective Goggles Full protective clothing with NOISH approved self contained breathing apparatus. 		
Environmental precaution	 Prevent soil and water pollution Substance must not be discharged into sewerage system Contain leaking substance and pump over in suitable containers Plug the leak, cut off the supply Dam up the liquid spill Curtail evaporation 		
Accidental Release Control Measures	 Inhalation of concentrated vapors may cause serious damage to nose, throat and lungs. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Swallowing may cause severe injury leading to death. Symptoms include sore throat, vomiting and diarrhea. During ingestion do not induce vomiting. Give large quantities of water or milk. Never give anything by mouth to unconscious person. Get medical help immediately. Contact with concentrated solution may cause serious damage to skin and eyes followed by skin sensitization and loss of sight. In case of contact with skin or eyes, immediately splash plenty of water for at least 15 minutes. If swallowed, if conscious, immediately induce vomiting. 		
Handling	 Observe very strict hygiene Avoid contact Use spark/explosion proof appliances and lighting system Take precautions against electrostatic charges Handle unidentified empty containers as full ones Do not discharge the waste into drain Water may be used to flush spills away from exposures and to dilute spills to non-flammable mixtures. Water diluted acid can react with metals to form hydrogen gas. 		



Ashok Alco - chem Limited (AACL)

Storage	 Keep container tightly closed Store in dry and dark area, protect against frost. Ventilation at floor level Fireproof storeroom Provide the tank with earthing. Additional Storage Precautions for Acetaldehyde: Cylinder should be stored upright and firmly secured to prevent falling.
Recommended	 Do not allow temperature above 125°F (51.67°C), where material is stored. Measure the concentration in air regularly
engineering controls	 Work under local / exhaust ventilation Store away from : heat sources, ignition sources, combustible materials, oxidizing agents, bases, metals, alcohols Use non-sparking type tools and equipment, including explosion proof ventilation. Area should be flame proof. Maintain Oxygen level above 19.5%